

PRODUCT SPECIFICATION

ESD Safety Shoes With Legging (Bootleg)



Product Description

InterWorld ESD Safety Shoe with legging are constructed with synthetic leather which are design for durability, flexibility and comfort. Its also design with adequate ventilation and with a base that minimize dirt trapping. Shoe sole is design with lighter weight with maximum gripping, particularly on wet floor and resistant to oils and fuels

Features static-dissipative inner sole and outer sole which provide continuous electrical contact of the foot to ground as required by ESD standards

InterWorld ESD Safety Shoe with legging are available in different styles and sizes.

Features

- Soft and supple, lint-free synthetic leather upper body
- Static-dissipative Polyurethane bottom sole (surface resistivity $10^5 - 10^9$ ohm/sq)
- Lighter ESD safety shoe without steel plate yet no compromise on safety
- Design with soft shoe lips to avoid foot fatigue
- Available in common sizes from 225 to 310mm.

InterWorld[®]

48541, Warm Springs Blvd. Fremont, CA 94539,
USA Tel: 510-226-6080 Fax: 510-226-6089
E-mail: ussales@interworldgroup.com Website: www.iwgh.com

Document No.: IWG-PS-ES-003
Issued Date: 01-April-19 Rev. A

PRODUCT SPECIFICATION

Application

- Ideal choice for semi-conductor, electronics, and any areas where ESD control is required.

IWG Part Number	Description	Packaging
32000-1145 until 32000-1152	Shoes, ESD, White, Legging, Synthetic leather upper, Polyurethane sole, size 225 to 300mm	1 pair per bag

Specifications

Colour	White
--------	-------

Dimensions

Shoe Length	Size 225, 230, 235, 240, 245, 250, 255, 260, 265, 270, 275, 280, 285, 290, 295, and 300mm
-------------	---

Material

Upper body	Synthetic leather
Outer sole	Static Dissipative Polyurethane
Bootleg	Yes, customize per customer's requirement

ESD Properties

STM 97.1-2015 – Resistance Measurement in Combination With a Person – Outer Sole	< 10 ⁹ ohm
STM 97.1-2015 – Resistance Measurement in Combination With a Person – Inner Sole	< 10 ⁹ ohm
Resistance to Ground (ESD S9.1-2014) From top surface of inner sole to groundable point through outer sole	< 10 ⁹ ohm
STM 97.2-2006 – Voltage Measurement in Combination With a Person	< 100 volts

InterWorld®

48541, Warm Springs Blvd. Fremont, CA 94539,
USA Tel: 510-226-6080 Fax: 510-226-6089
E-mail: ussales@interworldgroup.com Website: www.iwgh.com

Document No.: IWG-PS-ES-003
Issued Date: 01-April-19 Rev. A